LiFT Pack M-Series: M24

24V ADVANCED LITHIUM-ION BATTERY PACK

SWITCH TO THE NEW, HIGHER-PERFORMING AND LONGER-LASTING LITHIUM-ION BATTERY PACK

Dramatically Lowers Your Costs! Safer Technology! Improved Productivity!

ADVANCED LITHIUM-ION TECHNOLOGY

- Higher sustained power, with no voltage drop-off
- Fast charge in as little as one hour
- Safe No acid spills or combustible gas emissions
- Over 3500 cycles at 80% depth of discharge
- Up to 45% lower cost fewer replacements needed
- No battery swapping required for multi-shift applications
- Maintenance Free
- Typically uses 40% less energy

SOLUTIONS FOR Class III Equipment Including End Riders, Center Riders, & Walkie Stackers



fluxpower.com

POWER

SPECIFICATIONS LIFT Pack M-Series: M24

CALL 877-505-3589

LENCTH30.8 in /3.0 cm/WIDTH13.0 in /3.0 cm/HEIGHT31.0 in /3.0 cm/AVAILABLE CAPACITIES400 Ah (10 kWh)600 Ah (15 kWh)SYSTEM / NOMINAL VOLTAGE400 Ah (10 kWh)600 Ah (15 kWh)MAX CONTINUOUS CHARGE CURRENT (EXTERNAL)24 √ 2.5 √MAX CONTINUOUS DISCHARGE CURRENT32° F to 13° F √ 0.5 °C (10 °C			
HEICHT 31.0 in (78.7 cm) AVAILABLE CAPACITIES 400 Ah (10 kWh) 600 Ah (15 kWh) SYSTEM / NOMINAL VOLTACE 24 V / 25.6 V MAX CONTINUOUS CHARGE CURRENT (EXTERNAL) 280 A MAX CONTINUOUS DISCHARGE CURRENT 280 A CHARGE TEMPERATURE RANGE 32° F to 113° F (0° C to 45° C) DISCHARGE TEMPERATURE RANGE -4° F to 131° F (-20° C to 55° C) CABLE LENGTH AND POSITION (STANDARD) 24.0 in (61.0 cm) / Position C	LENGTH	30.8 in (78.2 cm)	
AVAILABLE CAPACITIES400 Ah (10 kWh)600 Ah (15 kWh)SYSTEM / NOMINAL VOLTACE24 V / 25.6 VMAX CONTINUOUS CHARGE CURRENT (EXTERNAL)280 AMAX CONTINUOUS DISCHARGE CURRENT280 ACHARGE TEMPERATURE RANGE32° F to 113° F (0° C to 45° C)DISCHARGE TEMPERATURE RANGE-4° F to 131° F (-20° C to 55° C)CABLE LENGTH AND POSITION (STANDARD)24.0 in (61.0 cm) / Position C	WIDTH	13.0 in (33.0 cm)	
SYSTEM / NOMINAL VOLTAGE24 V / 25.6 VMAX CONTINUOUS CHARGE CURRENT (EXTERNAL)280 AMAX CONTINUOUS DISCHARGE CURRENT280 ACHARGE TEMPERATURE RANGE32° F to 113° F (0° C to 45° C)DISCHARGE TEMPERATURE RANGE-4° F to 131° F (-20° C to 55° C)CABLE LENGTH AND POSITION (STANDARD)24.0 in (61.0 cm) / Position C	HEIGHT	31.0 in (78.7 cm)	
MAX CONTINUOUS CHARGE CURRENT (EXTERNAL)280 AMAX CONTINUOUS DISCHARGE CURRENT280 ACHARGE TEMPERATURE RANGE32°F to 113°F (0°C to 45°C)DISCHARGE TEMPERATURE RANGE-4°F to 131°F (-20°C to 55°C)CABLE LENGTH AND POSITION (STANDARD)24.0 in (61.0 cm) / Position C	AVAILABLE CAPACITIES	400 Ah (10 kWh)	600 Ah (15 kWh)
MAX CONTINUOUS DISCHARGE CURRENT280 ACHARGE TEMPERATURE RANGE32°F to 113°F (0°C to 45°C)DISCHARGE TEMPERATURE RANGE-4°F to 131°F (-20°C to 55°C)CABLE LENGTH AND POSITION (STANDARD)24.0 in (61.0 cm) / Position C	SYSTEM / NOMINAL VOLTAGE	24 V / 25.6 V	
CHARGE TEMPERATURE RANGE 32°F to 113°F (0°C to 45°C) DISCHARGE TEMPERATURE RANGE -4°F to 131°F (-20°C to 55°C) CABLE LENGTH AND POSITION (STANDARD) 24.0 in (61.0 cm) / Position C	MAX CONTINUOUS CHARGE CURRENT (EXTERNAL)	280 A	
DISCHARGE TEMPERATURE RANGE -4° F to 131° F (-20° C to 55° C) CABLE LENGTH AND POSITION (STANDARD) 24.0 in (61.0 cm) / Position C	MAX CONTINUOUS DISCHARGE CURRENT	280 A	
CABLE LENGTH AND POSITION (STANDARD) 24.0 in (61.0 cm) / Position C	CHARGE TEMPERATURE RANGE	32°F to 113°F (0°C to 45°C)	
	DISCHARGE TEMPERATURE RANGE	-4°F to 131°F (-20°C to 55°C)	
WEICHT 980 lbs (445 kg)	CABLE LENGTH AND POSITION (STANDARD)	24.0 in (61.0 cm) / Position C	
	WEIGHT	980 lbs (445 kg)	

HOW FLUX POWER TECHNOLOGY MAKES THE DIFFERENCE

BATTERY MANAGEMENT SYSTEM (BMS)

The integral BMS, which is UL Listed, was designed and developed in-house, assuring a fully optimized solution for demanding material handling applications. The patented BMS software ensures the battery provides peak performance at all times when in operation (even at low charge levels), delivers longer run times between charges, and maximizes the total battery lifespan. All Flux Power batteries are designed and built to meet UL standards.

FULL INTEGRATION

The LiFT Pack M-Series is capable of integrating with forklift trucks over CAN. This provides a seamless transition for operators when switching to lithium-ion. The integration features include:

- Accurate battery discharge indicator
- Lift lockout at low state of charge
- Early warning for safe shutdown

LITHIUM-ION CELLS

Flux Power has optimized the safety and performance of lithium-ion for material handling equipment and other industrial applications. Lithium Iron Phosphate (LiFePO4) cells were selected because they are one of the safest choices compared to other lithium-ion chemistries.

OPTIONS

- Integrated heaters for cold temperature applications
- 47A high efficiency onboard charger



Copyright © 2019 Flux Power, Inc. All rights reserved 955001 12/19

fluxpower.com