





LiFePO₄

IP56 RATED

SPECIFICATIONS | G-SERIES: GSE3

FULL INTEGRATION

Flux Power's 80 V lithium-ion batteries are designed to accommodate various ground support equipment through its modular design and its integral battery management system.

The patented BMS software ensures the battery provides peak performance at all times no matter how demanding the operation. Experience the next stage of power and efficiency with a fast ROI and a long battery lifespan.

TECHNICAL SPECIFICATIONS

- AVAILABLE CAPACITIES: 315 Ah (24.2 kWh)
- **SYSTEM (NOMINAL VOLTAGE):** 80 V (76.8 V)
- MAX CONTINOUS CHARGE CURRENT (EXTERNAL):
 150 A
- OPERATING TEMPERATURE RANGE: -22 °F to 113 °F (-30 °C to 45 °C)
 - * Size of battery depends on equipment with truck adapters available to meet OEM weight requirements. Make sure to ask your sales rep for more information.

PACK OPTIONS



SKYBMS TELEMATICS

Access detailed battery performance, monitor fleet activity, and view metrics instantly.



WEIGHT ADAPTERS

Truck adapters available to meet OEM weight requirements.



INTEGRATED HEATERS

Combat colder conditions with our state-of-the-art integrated heaters to keep peek performance.





